



ACCREDITATION CERTIFICATE

Issued under the authority of Bangladesh Accreditation Act, 2006
by Bangladesh Accreditation Board (BAB), Ministry of Industries to

Greentech Inspection Limited.

Maisha Tower, 5B, 131 Gabtoli

Mazar Road, Mirpur, Dhaka-1216, Bangladesh.

This is to certify that this

Inspection Body(Type-A)


is accredited in accordance with the international standard

ISO/IEC 17020:2012

in respect of the associated scope, subject to the terms and
conditions governing the relevant conformity assessment
body (CAB) accreditation.

Certificate Number : 05.016.22
Accreditation Date : 09 June 2022
Date of Issuance : 21 August 2025 (1st Renewal)
Date of Expiration : 08 June 2028




21.08.2025
M. A. Kamal Billah
Director General

This certificate must be returned on request; reproduction must follow BAB guidelines. For the specific scopes to which this accreditation applies, please refer to the Directory of CABs at BAB website.

SCOPE OF ACCREDITATION

(For Inspection Bodies)

CAB Name & Address: Greentech Inspection Limited., Address: Maisha Tower, 5B, 131 Gabtoli, Mazar Road, Mirpur, Dhaka-1216. Bangladesh.

Accreditation Standard: ISO/IEC 17020:2012

Certificate Number: 05.016.22

Last Amended on: NA

Amendment no: NA


Types : A

Accreditation Date: 09 June 2022

Issued on: 21 August 2025

Valid until: 08 June 2028

Head Office or primary location			Additional Locations (If different from Head Office)		
Maisha Tower, 5B, 131 Gabtoli, Mazar Road, Mirpur, Dhaka-1216			1	NA	
			2	NA	
			3	NA	
Type (A,B, C)	Inspection Category(Pro duct, Process, Services or Installation)	Inspection Field (and sub-fields)	Range of inspections	Stage of inspect ion	Inspection requirements or criteria
A	Service	Noise Level Assessment	30-130 dB	NA	In-house (GIL_SOP_01)
	Service	Light Level Assessment	0-200,000 lux		In-house (GIL_SOP_02)
	Service	Temperature Level Assessment	-20°C-1000°C /-4--1832°F		In-house (GIL_SOP_03)
	Service	Humidity Level Assessment	0-100% RH		In-house (GIL_SOP_04)
	Service	Stack Air Emission Assessment	Differential pressure flue gas draught -40 to +40 hPa Temperature: 0 to +600°C Draught: ±40 mbar Pressure: -200 to +200 mbar Efficiency measurement: 0 to 120% Flue gas loss (qA): 0 to 99.9% O ₂ : 0 to 30% CO: 0 to 5000 ppm CO ₂ : 0 to max NO _x : 0 to 1000 ppm NO: 0 to 250 ppm NO ₂ : 0 to 4000 ppm SO ₂ : 0 to 2000 ppm		In-house (GIL_SOP_05)
	Service	Ambient Air Quality Assessment	PM _{2.5} : 0-999 ug/M ³ PM ₁₀ : 0-999 µg /m ³ TVOC: (0.001-9.999Mg/M ³) HCHO: (0.001-1.999Mg/M ³) AQI: (0-500)		In-house (GIL_SOP_06)


Quality Manager

Head Office or primary location			Additional Locations (If different from Head Office)		
Maisha Tower, 5B, 131 Gabtoli, Mazar Road, Mirpur, Dhaka-1216			1	NA	
			2	NA	
			3	NA	
Type (A,B, C)	Inspection Category(Pro duct, Process, Services or Installation)	Inspection Field (and sub-fields)	Range of inspections	Stage of inspect ion	Inspection requirements or criteria
A			Temperature: -20 ~ +70[°C] Humidity: 0 ~ 100% CO: 0 to 1000 ppm O2: 0 to 30% vol SO2: 0 to 100 ppm NO2: 0 to 100 ppm	NA	
	Service	Indoor Air Quality Assessment/ Industrial Hygiene Assessment	PM2.5: 0-999 ug/M ³ PM10: 0-999 µg /m ³ TVOC: (0.001-9.999Mg/M ³) HCHO: (0.001-1.999Mg/M ³) AQI: (0-500) Temperature: -20 ~ +70 [°C] Humidity: 0 ~ 100% CO: 0 to 1000 ppm O2: 0 to 30% vol SO2: 0 to 100 ppm NO2: 0 to 100 ppm		In-house (GIL_SOP_07)

END



Quality Manager